

PHENOMENAL CREATIONS

800x1600mm



aboutUS

In an industry where some sellers focus on innovation, the other few choose to concentrate on variety, Commander has adopted a holistic strategy of encompassing all the attributes of the product. Commander epitomizes consumer-first approach with an enduring combination of innovation, unique variety and quality.

Since its inception in 2011, Commander tiles, based at Morbi in Gujarat, is one of the pioneer and dominant manufacturers cum exporters of premium glazed vitrified tiles. Commander has state-of-the-art manufacturing facility with latest technology machinery imported from Italy, Spain and China. At Commander, we believe in providing superior quality and services, further strengthening our relationship with consumers.

In tandem with an increasing demand of vitrified tiles, we have an installed capacity of 55,000 sq.m./day of GVT, PGVT, WALL TILES and Double Charge tiles spread across a humongous 65 acres land. We have collaborated with the largest Italian conglomerate, Sacmi for its press technology and installed System digital printing machine, which helps us yield innovative tiles with stunning designs and excellent quality. We constantly emphasize on new product development catering the dynamic and unique taste of our consumers.

20 Years of experience in ceramic industry

20m

Sq. mtrs. production per year

The structure, technology and the entire setup at Commander is in sync with the contemporary times. Innovation, progress, commitment and perfection are the four fundamental pillars of the company. Core values of the Commander team is a combination of intelligence, skills, knowledge and dedication. The people working at Commander love to invent and reinvent while exploring new concepts with the help of our state-of-the-art technology and a positive attitude.

The unmatched technical brilliance of our manufacturing units and genuine efforts of the man power has led us to the path of growth and progress. Marching ahead on the bright path of achievement we are bringing a new thought process for the best results. Ideas for the future!













An exceptional COIICTION

Commander provides an extraordinary collection of tiles that are available in diverse designs. These tiles are crafted to perfection to provide the ultimate comfort and luxurious experience with their fine functionalities and high-end quality.











High Strength



Random Designs



Maintenance Free



<0.08% water absorption



Eco Friendly



Chemical Resistant





Finishes

High gloss Black High Gloss Glossy Carving Rustic Rustic With Glossy Ink Prismatic Metallic Matt




High Gloss















Colour Moods LASTRA THE NEXT GEN SLAB






Black High Gloss FINISH



















LASTRA THE NEXT GEN SLAB




















Glossy	
Finish	



























LASTRA THE NEXT GEN SLAB













SEAMLESS


























SEAMLESS
















SEAMLESS
























LASTRA THE NEXT GEN SLAB
























Colour Moods LASTRA THE NEXT GEN SLAB












Colour Moods















Colour Moods











Regal Silver River Crema Faces 3



LASTRA THE NEXT GEN SLAB



SEAMLESS
















SEAMLESS





















SEAMLESS

















SEAMLESS









Colour Moods





SEAMLESS

SEAMLESS




















SEAMLESS


SEAMLESS









SEAMLESS

























































Regal Rainforest Crema












































SEAMLESS

SEAMLESS





LASTRA THE NEXT GEN SLAB








Actual Tile Image





Colour Moods









Colour Moods







Colour Moods








































SEAMLESS



Carving	
Finish	

Colour Moods




9 TIT

LASTRA THE NEXT GEN SLAB



Actual Tile Image



Rustic FINISH






Regal Symphony Blanco Faces 3








Regal Symphony Gris Faces 3








Rustic With Glossy Ink FINISH
















Collection





Metallic EFFECT







Regal Cloudy Metal Orange






Faces

















































Instructions

Handling

For handling the slabs, as well as for cutting and laying, Commander recommends the use of a kit of devices designed especially for large sizes. To increase rigidity and limit twisting, use a system composed of parallel and transverse guides





Reinforced Trolley for slab tile

Cutting & Drilling

Parallel And Transverse Guides

1. Side Cutting Process



1. Cutting Unit





1. Non Percussion Drill


3. Centre Drilling Process



1. Round Cut with Diamond Blade Drill




2. Cutting of Tile



2. Cut with Diamond Blade Angle Grinder



3. Refining Smooth Rough Edges With A Diamond Polishing Pad



3. Refining Smooth Rough Edges With A Diamond Polishing Pad

Laying & Levelling





1. Cement laying on Floor

2. Cement laying on Tile



3. Spacers + Leveller





5. After Levelling Process leave it for 8-10 hrs.

6. Remove Wedges ones it Dry

Floor Installation

- 1. First spread the cement mixer onto the floor substrate
- 2. At the same time, Apply the cement mixer onto the back of the slab with a tile trowel.
- 3. The recommended cement mixer is must be spread over in one direction only.
- 4. Using a trowel and following the same direction as previously applied to the back of the slab
- 5. Being careful to maintain a minimum joint of 3mm.
- 6. Tap the slab with a rubber trowel for a complete fixing, ensuring the air is expelled. It is recommended to start from the centre of the slabs and then move towards the edges.
- 7. Complete the laying operations using a suitable sealant, while keeping at least a 3mm joint through the use of spacers
- 8. To make this task easier, use the special device for pulling over the slabs, available on the market 9. Levelling wedges at each linear metre of the slabs are recommended
- 10. After Levelling Process leave it for 8-10 hours Remove Wedges ones it Dry







Cleaning And Maintenance

Lastra products are non porous (due to their high quality raw materials, stringent production parameters and state of the art technology), hence any dust or deposited waste cannot penetrate the surface.

For most cases only a damp cloth is sufficient for cleaning.

Regular cleaning highlights the aesthetic features of the surface and gives it exceptional shine.

For highly aggressive cleaning caused by some common food and substances follow the table below.

EXAMPLE
Detergent
Ammonia
Alcohol
Hydraulic Acid
Descaling Products
Hydraulic Acid
Ammonia Or Bleach
Ammonia Or Bleach
Alcohol
Hydraulic Acid
Alcohol
Bleach
Detergent
Alcohol
Bleach

Disclaimer: The aim of this manual is to offer helpful suggestions about handling and maintaining Lastra slabs. Due to nature of sintered ceramic material, it is highly advisable to consult an expert for these purposes. Commander cannot be held responsible for any damage resulting from using the information and suggestions contained in this technical manual.

Technical Specification of GVT

CHARACTERISTIC	International Standards Group B1a- ISO 13006 Annx. G.	MEAN VALUE OF COMMANDER	TEST METHOD
Deviation In Length	± 0.60%	± 0.10%	ISO-10545-2
Deviation In Thickness	± 5.00%	± 4.00%	ISO-10545-2
Straightness Of Sides	± 0.50%	± 0.10%	ISO-10545-2
Rectangularity	± 0.60%	± 0.10%	ISO-10545-2
Surface Flatness	± 0.50%	± 0.15%	ISO-10545-2
Surface Quality (%)	A minimum of 95% of the tiles shall be free from visible defects that would impair the appearance of a major area of tile	95% Free from Visible Defects	
Scratch Hardness of Surface (Moh's scale)	Min. 6	Min. 6	ISO-10545-2
Modulus of Rupture	> 35N/mm3	> 40N/mm²	ISO-10545-4
Breaking Strength	> 1300 N	> 1500 N	ISO-10545-4
Water Absorption	< 0.50%	< 0.08%	ISO-10545-3
Stain Resistance	Stain Resistant	Stain Resistant	ISO-10545-14
Chemical Resistance	No Damage	No Damage	ISO-10545-13
Thermal Expansion	< 9 x 10-6	< 7 x 10-6	ISO-10545-8
Moisture Expansion	Nil	Nil	ISO-10545-10
Thermal Shock Resistance	No Damage	No Damage	ISO-10545-9
Resistance to Surface Abrasion	Manufacturer to State Abrasion Class	PEI class 3-5	ISO-10545-7
Bulk Density	> 2.00	> 2.20	ISO-10545-3

Packing Detail

Products	Size	Pcs. /
LASTRA	800x1600mm	2 pc

Note: Colour Shown are as accurate as the limitations of the printing process will allow. Prospective customers are advised to inspect a sample of the tile before ordering. Every effort has been made to ensure the accuracy of the information given. However, the company reserve the right to change the specifications without prior notice. Sometime variations in shade or size being inherent to ceramic industry may occur. Before fixing, we advise you to follow the fixing instructions on the cartons of the tiles as no responsibility can be accepted by the company once the tiles have been fixed.



/ Box	Area / Box	Wt./Box
CS.	2.56 sq. mtr.	55 kg.





COMMANDER VITRIFIED PVT. LTD. 8-A N.H., At. Sartanpar, Ta. Wankaner - 363 621, Dist. Morbi, Gujarat, INDIA

+91 95123 20066 COMMANDERVITRIFIED.COM